

Typhoon 300



Features

- Robust electrical isolated heating element
- Compact design and easy to install
- Simple electrical connection (fan and heater combined)
- Fixing 35mm DIN-rail mount
- Complies RoHS (EU Directive 2002/95/EC)

DBK's knowledge of thermal management gives us the experience to guide and support you with your technical challenges - we can manage the complete project from concept to full production release.

Type		Typhoon 300 230 V	Typhoon 300 115 V
Nominal Power at 25°C Nominal	W	300 - 350	300 - 350
Input Voltage	V	230 VAC	115VAC
Nominal Input Frequency	Hz	50	60
Operating Temperature Range		-10°C to +70°C	-10°C to +70°C
Storage Temperature Range		-40°C to +70°C	-40°C to +70°C
Fan Lifetime (MTTF at 30°C)	h	606,120	606,120
Fan Volumetric Flow	m ³ /h	40	50
approximate Weight	g	890	890
Dimensions	Cross section mm	85 x 103	85 x 103
	Length mm	145	145
Lead Wires Length	mm	1000	1000
Ingress Protection (EN60529)		IP 20	IP 20
Electrical Protection Class		I	I
Recommended Fuse, Time	A	10	10
Delay Finger Guard at inlet and		Yes	Yes

